## Amendments to the Claims:

Please cancel Claims 74 through 76 without prejudice to or disclaimer of the subject matter recited therein.

Please amend Claims 61, 63, 65, 66, and 76 through 80 to read, as follows.

Claims 1 through 60. (Canceled)

61. (Currently Amended) A toner supply container detachably mountable to an image forming apparatus, said container comprising:

a container body for accommodating toner;

a discharge opening, which is provided in said container body, for permitting discharge of the toner;

a sealing member for unsealably sealing said discharge opening, wherein said sealing member includes an engageable <u>projection</u>, which is <u>projection</u> engageable with an engaging member provided in the image forming apparatus, and a supporting member for displaceably supporting said engageable projection,

wherein when said sealing member is moved relative to said container body away therefrom to unseal said discharge opening, said engageable projection is engaged with the engaging member; and

a releasing projection, provided in said supporting member, for receiving, from a releasing member provided in the image forming apparatus, a force for displacing said engageable projection in a direction of disengagement from the engaging member.

- 62. (Previously Presented) A container according to Claim 61, wherein said engageable projection is engageable and disengageable relative to the engaging member substantially without receiving a force in a direction away from the engaging member.
- 63. (Currently Amended) A container according to Claim 61, wherein said releasing projection is constructed so as to receive a releasing force from said releasing member, projection, which is in a form of a slidable hollow-cylindrical shape, and said releasing projection projects from said engageable projection.
- 64. (Previously Presented) A container according to Claim 63, wherein said releasing projection is provided at a position nearer to a base portion of said supporting member than said engageable projection.
- 65. (Currently Amended) A container according to Claim 61, wherein a plurality of [[such]] supporting members are arranged in a circumferential direction at discrete positions.
- 66. (Currently Amended) A container according to Claim 61, wherein four of such supporting members are arranged in a circumferential direction with a 90° spacing therebetween.
- 67. (Previously Presented) A container according to Claim 61, wherein said engageable projection and said releasing projection have tapered surfaces.

- 68. (Previously Presented) A container according to Claim 61, wherein said supporting member is made of a resin material and is elastically restorable in a direction of said engageable projection engaging with the engaging member.
- 69. (Previously Presented) A container according to Claim 68, wherein said supporting member has a smaller thickness at a base portion than at a free end portion thereof.
- 70. (**Previously Presented**) A container according to Claim 68, wherein said supporting member is provided at each side of said engageable projection with a slit extending to a free end of said supporting member.
- 71. (Previously Presented) A container according to Claim 61, further comprising an urging member for urging said supporting member in a direction of said engageable projection engaging the engaging member.
- 72. (Previously Presented) A container according to Claim 61, wherein said engageable projection is engageable with the engaging member in a snap-fit fashion.
- 73. (Previously Presented) A container according to Claim 61, wherein after said discharge opening is resealed, said engageable projection is disengaged from the engaging member by a force received by said releasing projection.

- 74. (Canceled)
- 75. (Canceled)
- 76. (Canceled)
- 77. (Currently Amended) A toner supply container detachably mountable to an image forming apparatus, said container comprising:

a container body for accommodating toner;

a discharge opening, which is provided in said container body, for permitting discharge of the toner; and

a sealing member for unsealably sealing said discharge opening, wherein said sealing member has an engageable projection, which is engageable with an engaging member provided in the image forming apparatus in a snap-fit fashion,

wherein when said sealing member is moved relative to said container body away therefrom to unseal said discharge opening, said engageable projection is engaged with the engaging member, and

wherein said engageable projection is disengageable with the engaging member by a releasing member provided in the image forming apparatus substantially without receiving a force in a direction away from the engaging member.

78. (Currently Amended) A sealing member for sealing a toner discharge opening of a toner supply container detachably mountable to an image forming apparatus, said sealing member comprising:

a sealing portion for sealing the toner discharge opening;

an engageable <u>projection</u>, <u>which is projection</u> engageable with an engaging member provided in the image forming apparatus;

a supporting portion for displaceably supporting said engageable projection,
wherein when said sealing portion is moved relative to the container away
therefrom to unseal said discharge opening, said engageable projection is engaged with the
engaging member; and

a releasing projection, provided in said supporting portion, for receiving, from a releasing member provided in the image forming apparatus, a force for displacing said engageable projection in a direction of disengagement from the engaging member.

79. (Currently Amended) A sealing member for sealing a toner discharge opening of a toner supply container detachably mountable to an image forming apparatus, said sealing member comprising:

a sealing portion for sealing the toner discharge opening; and

an engageable <u>projection</u>, <u>which is projection</u> engageable with an engaging member provided in the image forming apparatus in a snap-fit fashion,

wherein when said sealing portion is moved relative to the container away therefrom to unseal the discharge opening, said engageable projection is engaged with the engaging member, and

wherein said engageable projection is disengageable with the engaging member by a releasing member provided in the image forming apparatus substantially without receiving a force in a direction away from the engaging member.

80. (Currently Amended) A toner supply container detachably mountable to an image forming apparatus, said container comprising:

a container body for accommodating toner;

a discharge opening, which is provided in said container body, for permitting discharge of the toner;

an engageable <u>projection</u>, <u>which is projection</u> engageable with an engaging member provided in the image forming apparatus to substantially fix a position of said discharge opening; [[and]]

a supporting member for displaceably supporting said engageable projection, wherein when the toner is supplied into the image forming apparatus from said toner supply container, said engageable projection is being engaged with the engaging member; and member, and

a releasing portion, provided in said supporting member, for receiving, from a releasing member provided in the image forming apparatus, a force for displacing said engageable projection in a direction of disengaging from the engaging member.